

a² unit 21, 22 is reduced between the back support 132 and the construction bar 151. So, the more inclination locking means 23 provided on the side supporting unit 21, 22, the more inclined angles between the back support 132 and the seat support 131 can be adjusted.--

Please replace the paragraph beginning at page 7, line 15, with the following rewritten paragraph:

a³ --As shown in Fig. 5, the two inclination locking means 23' are spacedly affixed to two vertical halves of the respective side supporting unit 21', 22' wherein one of the first locking elements 231' is affixed on the side supporting unit 21', 22' closed to the respective vertical side of the back support 132' and the corresponding second locking element 232' is affixed on a mid-portion of the side supporting unit 21', 22'. Another first locking element 231' is affixed to the mid-portion of the side supporting unit 21', 22' and the corresponding second locking element 232' is affixed on the side supporting unit 21', 22' closed to the construction bar 151'.--

IN THE CLAIMS:

Please cancel claims of record 1 to 20 without prejudice or disclaimer and replace with the newly drafted claims as follows:

1. A stroller, comprising:

a⁴ a supporting frame, a seat frame supported by said supporting frame, and a handle frame having two construction bars upwardly extended from said supporting frame wherein said seat frame comprises a seat support horizontally supported by said supporting frame and a back support upwardly extended from said seat support; and

an adjustable seat back arrangement, which comprises:

two side supporting units sidewardly extended from two vertical sides of said back support to said two construction bars respectively for folding said back support between an upright position and a fully extended position, wherein in said upright position, said back support is vertically extended from said seat support, and in said fully